



GUTEX® Standard-n Data Sheet



Photographic images are property of GUTEX archive; WOLF Haus

GUTEX Standard-n is suitable for diverse interior applications.

Technical Data	Standard-n
Joint type	Butted
Thickness (mm)	6/8/10/12/15/18
Length x width (mm)	2500 x 1000/1500
Square metres per board (m ²)	2.5/3.75
Weight per m ² (kg)	1.5 - 4.5
Weight per board (kg)	3.75 - 16.88
Boards per pallet	170/130/100/80/70/55
Square metres per pallet (m ²)	137.5 - 637.5
Weight per pallet (kg)	700/1000
Bulk density (kg/m ³)	250
Vapour diffusion factor (μ)	5
sd-value (m)	0.03/0.04/0.05/0.06/0.075/0.09
Compressive stress/ strength (kPa)	100
Short-term water absorption (kg/m ²)	≤ 2.0
Air flow resistivity (kPa s/m ²)	100
Specific heat capacity (J/kgK)	2100
Fire reaction Euro Class as per DIN EN 13501-1	E

European Union	
Nominal thermal conductivity λ _D (W/mK)	0.046
Nominal thermal resistance R _D (m ² K/W)	0.10/0.15/0.20/0.25/0.30/0.35



Standard-n designation: WF-ENI 3171-T5-WS2, 0-CS (10/Y) 100-MU5-AF100

German disposal category: A2 (treated wood; without non-halogenated organic compounds)

Code number as per AVV: 030105; 170201

Composition

- Manufactured from untreated Black Forest spruce and fir
- 1.5% paraffin (hydrophobising agent)

Applications

- Thermal and acoustic insulation of ceilings and floors
- Finishing of living spaces under the roof
- Finishing of dry cellar spaces
- Other uses in the woodworking industry, including pinboards, portable partition walls and screens, door inlays, packaging material, etc.
- Installation over loose floor fill

Advantages

- Ideal for upgrading the thermal insulation of existing structures
- Superior thermal storage capacity provides outstanding insulation against heat in the summer and cold in winter.
- Good acoustic insulation
- Regulates humidity
- Water vapour diffusion permeable
- Wood is a sustainable, recyclable natural resource
- Made in Germany
- Biologically safe (natureplus® certified)

Installation

- Store and install this product dry.
- For best cutting results, use a handheld circular saw with vacuum fitting to cut boards thicker than 10 mm and a carpet knife for boards under 10 mm.
- Offset the joints if installing multiple layers.
- Vacuum off the dust in accordance with applicable workplace safety regulations or practices.

All rights reserved. Henselmann GmbH + Co KG is not liable for any damage resulting from error or misprinting. The technical data provided herein is subject to change. Although all of the information was current at the time of its publication, the publication of superseding information renders the old information invalid.

The suitability of this product for applications not specified in this data sheet is not guaranteed. Warranty and liability claims are subject to the terms of Gutex's General Terms of Business.



NATURALLY MADE FROM WOOD